

DORSEY STANDARD BORE GAGES

www.dorseymetrology.com

DS-

B1-

1

2

1

0

4

-12

Style

Indicator

Contacts

Indicator

Gage Size

A Length

GAGE SIZE	INDICATOR GRADUATION	HIGH AMPLIFICATION INDICATOR	PART NUMBER	TRADITIONAL INDICATOR	TRADITIONAL PART NUMBER
1.00 - 1.53" 25.4 - 38.9mm	.00005 ^s	DS-2I4-005	DS-B1-10102		
	.0001 ^s	DS-2I9-01	DS-B1-11102		
	.0001"	DS-2I50-01	DS-B1-12102	DS-2DM025-01	DS-B2-12102
	.00025"	DS-2I100-025	DS-B1-10112		
	.0005 ^s	DS-2I40-05	DS-B1-13102		
	.0005"	DS-2I100-05	DS-B1-14102	DS-2DM050-05	DS-B2-14102
	NONE	LESS INDICATING UNIT	DS-B1-15102		
	0.010mm ^s	DS-2I10-01mm	DS-B1-16102	DS-2DM5-01mm	DS-B2-16102
	0.005mm	DS-2I25-005mm	DS-B1-17102	DS-2DM012-005mm	DS-B2-17102
	0.002mm	DS-2I10-002mm	DS-B1-18102	DS-2DM005-002mm	DS-B2-18102
	0.002mm ^s	DS-2I02-002mm	DS-B1-19102		
	0.001mm ^s	DS-2I01-001mm	DS-B1-10122		
	.0001" / .002mm ^s	S2I.M	DS-B1-12102M		
	.00005" / 0.001mm	DIGITAL	DS-B5-10102		
1.50 - 2.16" 38.1 - 54.8mm	.00005 ^s	DS-2I4-005	DS-B1-10103		
	.0001 ^s	DS-2I9-01	DS-B1-11103		
	.0001"	DS-2I50-01	DS-B1-12103	DS-2DM025-01	DS-B2-12103
	.00025"	DS-2I100-025	DS-B1-10113		
	.0005 ^s	DS-2I40-05	DS-B1-13103		
	.0005"	DS-2I100-05	DS-B1-14103	DS-2DM050-05	DS-B2-14103
	NONE		DS-B1-15103		
	0.010mm ^s	DS-2I10-01mm	DS-B1-16103	DS-2DM5-01mm	DS-B2-16103
	0.005mm	DS-2I25-005mm	DS-B1-17103	DS-2DM012-005mm	DS-B2-17103
	0.002mm	DS-2I10-002mm	DS-B1-18103	DS-2DM005-002mm	DS-B2-18103
	0.002mm ^s	DS-2I02-002mm	DS-B1-19103		
	0.001mm ^s	DS-2I01-001mm	DS-B1-10123		
	.0001" / .002mm ^s	S2I.M	DS-B1-12103M		
	.00005" / 0.001mm	DIGITAL	DS-B5-10103		

GAGE SIZE	INDICATOR GRADUATION	HIGH AMPLIFICATION INDICATOR	PART NUMBER	TRADITIONAL INDICATOR	TRADITIONAL PART NUMBER
2.12 - 3.13" 54.0 - 79.5mm	.00005 ^s	DS-2I4-005	DS-B1-10104		
	.0001 ^s	DS-2I9-01	DS-B1-11104		
	.0001"	DS-2I50-01	DS-B1-12104	DS-2DM025-01	DS-B2-12104
	.00025"	DS-2I100-025	DS-B1-10114		
	.0005 ^s	DS-2I40-05	DS-B1-13104		
	.0005"	DS-2I100-05	DS-B1-14104	DS-2DM050-05	DS-B2-14104
	NONE		DS-B1-15104		
	0.010mm ^s	DS-2I10-01mm	DS-B1-16104	DS-2DM5-01mm	DS-B2-16104
	0.005mm	DS-2I25-005mm	DS-B1-17104	DS-2DM012-005mm	DS-B2-17104
	0.002mm	DS-2I02-002mm	DS-B1-18104	DS-2DM005-002mm	DS-B2-18104
	0.002mm ^s	DS-2I02-002mm	DS-B1-19104		
	0.001mm ^s	DS-2I01-001mm	DS-B1-10124		
	.0001" / .002mm ^s	S2I.M	DS-B1-12104M		
	.00005" / 0.001mm	DIGITAL	DS-B5-10104		
3.09 - 6.13" 78.5 - 156mm	.00005 ^s	DS-2I4-005	DS-B1-10105		
	.0001 ^s	DS-2I9-01	DS-B1-11105		
	.0001"	DS-2I50-01	DS-B1-12105	DS-2DM025-01	DS-B2-12105
	.00025"	DS-2I100-025	DS-B1-10115		
	.0005 ^s	DS-2I40-05	DS-B1-13105		
	.0005"	DS-2I100-05	DS-B1-14105	DS-2DM050-05	DS-B2-14105
	NONE		DS-B1-15105		
	0.010mm ^s	DS-2I10-01mm	DS-B1-16105	DS-2DM5-01mm	DS-B2-16105
	0.005mm	DS-2I25-005mm	DS-B1-17105	DS-2DM012-005mm	DS-B2-17105
	0.002mm	DS-2I02-002mm	DS-B1-18105	DS-2DM005-002mm	DS-B2-18105
	0.002mm ^s	DS-2I02-002mm	DS-B1-19105		
	0.001mm ^s	DS-2I01-001mm	DS-B1-10125		
	.0001" / .002mm ^s	S2I.M	DS-B1-12105M		
	.00005" / 0.001mm	DIGITAL	DS-B5-10105		

^s = single revolution indicator.

FEATURES:

- ✓ Range ext up to 36" are available. Larger than 36" available by special request.
- ✓ All models come with steel contacts but carbide and diamond contacts are also available.

OPTIONAL CONTACT POINTS

OPTION	1	2	4	5	7	8
Gaging Contact	Steel	Carbide	Diamond	Carbide	Diamond	Offset Contact Configuration
Centralizing Contact	Steel	Steel	Steel	Carbide	Carbide	H Dimension